NO. REVISIONS	APPROVED	DATE
	<u> </u>	
** LUMINARE: DECORATIVE CAST AND SPUI 150' OF ALIM ARM ** LUMINARE: DECORATIVE CAST AND SPUI DESIGNED FOR WEATHERINGTH PERFORM ** GLOBE: UPAL ACTULE WITH COLOR BA GLOBE: UPAL ACTULE WITH COLOR BA ** BALLAST: HICH PRESSURE SODIUM (70 REQUIRED) - VOLTAGE AS REQUIRED - ** LAMP: METAL HALDE OR HIGH PRESSUR AS REQUIRED) ** PUEL: PGB 306-14 (5° DIA X 14'-0" WITH DECORATIVE CAST ALUM, BASE, IN AND HANDHOLE COVER. ** FINISH: POWDER COATED - SHERMIN W ROCKWOOD SASH GREEN #SW 2810 ** U.L.: ALL ELECTRICAL COMPONENTS SH. ** 1500 ** WEATHERSTPICOF DUPLEX RECEPTAGLE.	ANCE. ID ON UPPER PORTIO WATT — MAXIMUM WA MOUNTED IN LUMINA E SODIUM (MAXIMUM X 0.250 WALL FLUTE CLUDING BASE PLATE,	N OF TTAGE AS IRE HEAD WATTAGE TO ALUM.) HANDHOLE,

NOTES:

- MANUFACTURED 8Y DELTA LIGHTING SYSTEMS INC. OR EQUAL.
 FOR FOUNDATION DETAIL SEE STANDARD DRAWING NO. 907 (FOUNDATION TYPE "A")
 LAMP WATTAGE AND TYPE SUBJECT TO APPROVAL OF THE CITY ENGINEER.
 LAMP VOLTAGE SHALL BE AS REQUIRED TO CONNECT TO EXISTING ELECTRICAL SYSTEM OR 120 VOLT FOR NEW SYSTEMS.

CITY OF PALM SPRINGS PUBLIC WORKS & ENGINEERING DEPARTMENT	APPROVED: DATE: 10/18/07 _ 28931	
SINGLE PARKING LOT LIGHT	DRAWN BY: G.F.F.	FILE NO. STANDARDS
	CHECKED BY: M.L.F.	DWG. NO. 910